

Ceiling-mounted Indoor AP Series

WAP2100-T512



AI-driven



Cloud-based provisioning



Product Overview

BDCOM WAP2100-T512 is the BDCOM-developed ceiling-mounted wireless AP oriented for medium and high-density wireless scenarios such as enterprises, campus, hospitals, governments, hotels, and smart buildings.

WAP2100-T512 is designed with high-performance RF chip solution, with high throughput and strong concurrent access capability. WAP2100-T512 stands out with the built-in omnidirectional MIMO high-power antenna to meet the wireless coverage to the greatest extent. WAP2100-T512 supports both POE and Adaptor power supply solutions. It has a beautiful appearance and can be widely used for ceiling-mounting in various occasions such as gypsum board and cement roof. Therefore, WAP2100-T512 is your best choice for building an economical wireless network solution.

Product Characteristics

High-performance Wireless Solutions

WAP2100-T512 is built with high-performance wireless chipset, and supports 802.11a/b/g/n/ac/wave2 protocols, with high throughput and good stability. The 2.4G and 5G devices can support 1267Mbps air interface bandwidth to satisfy up to 60 users with service access, with strong concurrency capability.

WAP2100-T512 supports wireless load balancing. In high-density access scenarios, WAP2100-T512 can achieve reasonable allocation of terminals within a single AP through the 2.4GHz and 5GHz spectrum while ensuring balanced traffic distribution among multiple APs to avoid congestion, which enables the AP to access more end users, and provides the better Internet service.

Product Characteristics

Powerful Automatic Network Optimization

WAP2100-T512 supports wired and wireless QoS, automatic terminal identification, automatic channel selection, automatic power adjustment, dynamic receiving sensitivity and other carrier-level network optimization features while accessing a large number of users, which serves enterprises with easy-to-use and practical WLAN.

WAP2100-T512 can also cooperate with WSC6100 series wireless controllers to achieve the "one-key wireless automatic optimization" and "background automatic optimization", ensuring that users complete network tuning by themselves when the wireless environment changes, without waiting for manufacturers or agents to come to service.

Comprehensive Security Features

WAP2100-T512 supports WEP/WPA/WAP2 access modes, wireless IPS/IDS, the layer-2 user isolation, and centralized ACL control.

WAP2100-T512 supports docking with WSC6100 wireless AC and cloud platform, provides rich and practical diversified authentication functions for computers, mobile phones, tablets and other terminals, to facilitate user access authentication.

WAP2100-T512 provides illegal AP detection and subsequent processing, wireless attack defense, static black and white lists, to reduce the illegal intrusion on wireless networks.

User-friendly Design Details

WAP2100-T512 is equipped with LED controllable design: the LED lights can be turned off during the night break to avoid irritating the eyes; all the LED lights can be turned on to improve the operation efficiency during the network inspection. All the LEDs can be controlled in batches through the AC, and can also be switched individually with each AP button, which is very flexible and convenient.


WAP2100-T512 and mounting bracket adopt ultra-thin shape, and the network port is also designed to be retracted and hidden. The well-installed AP can be better integrated with the surroundings to ensure beauty and cleanliness.

Rich Manageable Features

WAP2100-T512 supports the integrated design of fat and thin APs, which can be individually configured, and can also be connected to BDCOM WSC6100 series wireless ACs to realize CLI, Web, SNMP management.

WAP2100-T512 can also be managed through the BDCOM cloud-based operation platform (COP) to achieve unified management of AC, switches, routers, security and other products, greatly improving the efficiency of operation and maintenance.

Application Diagram



Model



WAP2100-T512

2.4GHz	802.11ac MiMO 2*2 400Mbps
5GHz	802.11ac wave2 MiMO 2*2 867Mbps
coverage	200m ²

System Performance

Item	WAP2100-T512
Weight	400(g)
Mounting method	Ceiling
Dimensions	168x168x32(mm) (excluding accessories)
Ethernet port	1 GE WAN port (POE) 1 GE LAN port
Local power supply	POE input or 12V DC
PoE power supply	802.3at
Antenna type	Built-in, Omni-direction
Antenna gain	2.4G: 3dBi 5G: 3dBi
Operating frequency bands	802.11a/n/ac : 5.725GHz-5.850GHz ; 5.15-5.35GHz 802.11b/g/n/ac : 2.4GHz-2.483GHz
Wi-Fi data rate	2.4G: 2*2 11n 400Mbps 5G: 2*2 11ac 867Mbps
Maximum total transmitting power (The actual transmission power is subject to relevant regulations.)	2.4 GHz: 23 dBm (combined power) 5 GHz: 23 dBm (combined power)
Modulation technology	OFDM : BPSK@6/9Mbps, QPSK@12/18Mbps, 16-QAM@24Mbps, 64-QAM@48/54Mbps DSSS : DBPSK@1Mbps, DQPSK@2Mbps, CCK@5.5/11Mbps MIMO-OFDM (11n): MCS 0-15 MIMO-OFDM (11ac): MCS 0-9

System Performance

Item	WAP2100-T512
Modulation mode	11b: DSS: CCK@5.5/11Mbps, DQPSK@2Mbps, DBPSK@1Mbps 11a/g: OFDM: 64QAM@48/54Mbps, 16QAM@24Mbps, QPSK@12/18Mbps, BPSK@6/9Mbps 11nMIMO-OFDM: BPSK, QPSK, 16QAM, 64QAM 11ac/ac wave2: MIMO-OFDM: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Power adjustment	Automatic
Reset	Supported
Status LED	on / Blinking/ error
Operating temperature / Storage temperature	-10°C~40°C/-40°C~70°C
Operating humidity / Storage humidity	10%~95% (non-condensing)
Protection class	IP41
Power consumption	<12W
MTBF	>250000H

Software specifications

802.11ac compliance	Operating frequency bands	5GHz
	A-MPDU	Supported
	A-MSDU	Supported
	Transmit Beamforming (TxBF)	Supported
	Maximum Likelihood Demodulation (MLD)	Supported
	Maximum Ratio Combining (MRC)	Supported
	Space-Time Block Code (STBC)	Supported
	Low Density Parity Check Coding (LDPC)	Supported
MU-MIMO	Supported	
802.11n compliance	Operating frequency bands	2.4GHz+5GHz
	A-MPDU	Supported
	Maximum Likelihood Demodulation (MLD)	Supported
	Transmit Beamforming (TxBF)	Supported
	Maximum Ratio Combining (MRC)	Supported
	Space-Time Block Code (STBC)	Supported
	Low Density Parity Check Coding (LDPC)	Supported
	Maximum number of users per band	128

Software specifications

WLAN	WPA-PSK/WPA2-PSK/WPA3-PSK	Supported
	RTS/CTS	Supported
	Guest network	Supported
	Smart device SSID	Supported
	Wired networking	Automatic detection and authorization
	Wireless Mesh networking	Automatic detection and authorization
	Automatic path switching	Supported
	Automatic link fault detection and recovery	Supported
Advanced networking features	Automatic network-wide channel adjustment	Supported
	Automatic network-wide bandwidth adjustment	Supported
	Automatic network-wide power adjustment	Supported
	Automatic network management	Automatic networking with distributed APs, which allows you to add or replace APs as needed
Security policy	Encryption	AES
	802.11i	Supported
	Authentication	MAC Address/PSK
	Client isolation	1. Layer-2 wireless client isolation 2. SSID isolation
	Forwarding security	Packet filter, MAC address filter, and broadcast storm suppression
	SSID-VLAN binding	Supported
	Management frame protection (802.11w)	Supported
	802.11e	WMM
Advanced Wi-Fi features	Priority	Ethernet port 802.1P identification and marking Mapping from wireless priorities to wired priorities
	AI-QoS	Mapping based on application traffic and air interface queue

Software specifications

	Automatic channel/bandwidth/power selection	Supported
Advanced Wi-Fi features	Load balancing	Based on traffic / number of users / bands / air interface load
	802.11k / 802.11v / 802.11r	Supported
	AP steering	Supported
	Band steering	Supported
	Packet-by-packet power control	Supported
	Multicast enhancement	Multicast-to-unicast (IPv4)
	Inter-node Beamforming+	Supported
Power saving	PPC	Supported
	Green AP mode	Supported
	Dynamic MIMO power saving	Supported
	E-APSD	Supported
	WMM Power Save	Supported
Installation, management, and maintenance	Local management with app / Remote management	Supported
	Cloud AC Engine	Supported
	Local AC management	Supported
	Remote maintenance	Supported
	AP locating	Supported

Technical Specifications

Working mode

- Supports AP Mode
- Routing mode
- Bridging Mode

IP functions

- Supports IPv4, DHCP, NTP protocols
- Supports static IP allocation, dynamic DHCP and PPPoE dial-up

Wireless management

- Supports CAPWAP management protocol
- Supports Option43, DNS to discover AC
- Supports Layer 2 and Layer 3 networking of AC and AP
- Supports cross-NAT of AC and AP
- Supports Layer 2 and Layer 3 user roaming
- Supports clock, version and configuration synchronization of AC and AP

Application added

- Supports for RTLS probes
- Supports docking wireless positioning system

Wireless access

- Supports 802.11 protocol suite
- Supports multiple SSID management, Chinese SSID and SSID hiding
- Supports no SSID, VLAN binding function
- Supports SSID-based user limit and isolation
- Supports each SSID to specify the parameter template separately
- Supports country code setting

User authentication

- Supports local authentication and Cloud authentication
- Supports multiple authentication methods such as local account, SMS, WeChat, and voucher
- Supports user black and white lists
- Supports account-based access period control and bandwidth control

Security

- Supports PSK authentication method
- Supports WEP, WPA, WPA2, wireless encryption
- Supports IP-based, MAC-based filtration
- Supports DDoS, De-Auth anti-attack
- Supports Rogue AP detection

QoS

- Supports 802.11e/WMM
- Supports global trac rate limit
- Supports AP-based, VLAN-based, User-based trac rate limit
- Supports frequency-based, AP-based flow load balancing

Wireless optimization

- Supports one-click network optimization, customs wireless RF parameters
- Default 8 wireless scene templates, supports user-defined templates
- Supports 5G prior access, supports restrict access of lowrate users

Management and maintenance

- Supports traditional device management such as Telnet, SSH, Web, SNMP and TR069
- Supports ping, tracer, debug and other diagnostic tools templates
- Supports CAPWAP-based AC centralized management
- Supports COP unified management
- Support AP indicator on and off

Ordering Information

WAP2100-T512

WAP2100-T512 Ceiling-mounted Intelligent WiFi5 AP (2 GE ports, 802.11 a/b/g/n/ac/wave2, 1267Mbps Wireless, built-in antenna, supports POE and adaptor power input, excluding PSE and power adaptor)

Copyright © Shanghai Baud Data Communication Co., LTD.2023. All Rights Reserved.

This document is BDCOM Public Information. BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time.
www.bdc.com.cn

